



## **WARRANTY for Kynar 500® PVDF resin-based paint**

American Warming and Ventilating warrants our Kynar 500® PVDF resin-based finish on aluminum for (20) twenty years. In addition to meeting or exceeding AAMA 2605 standards, the following standards will be met:

- A. WILL NOT chalk in excess of ASTM-D-659-80 number eight (8) rating, determined by the procedure outlined in ASTM-D-659-80 specification test.
- B. WILL NOT change color more than five (5.0) Delta E units as determined by ASTM method D-2244-79.
- C. WILL NOT crack, check, or peel (lose adhesion). But this does not include minute fracturing which may occur in proper fabrication of the building parts.

### **NOTES ON FIELD REPAIRS AND CLEANING**

American Warming and Ventilating cannot warrant any field painting done to our louvers. For touch-up and minor field repairs, American Warming and Ventilating can supply small quantities of matching air-dry Kynar 500® PVDF resin-based finish on request. For large areas or refinishing the entire louver, contact American Warming and Ventilating Customer Service. The surface must be clean and free of dirt or contaminants before any paint is applied to the Kynar 500® PVDF resin-based finish surface.

**WARNING!** Do not use Acetone to clean the surface of the Kynar 500® PVDF resin-based finish or use paints, which may contain Acetone. Also do not use any Lacquer type paints on the surface of the Kynar 500® PVDF resin-based finish. **These chemicals may permanently damage the Kynar 500® PVDF resin-based finish and VOIDS the warranty.**